

sprint evolution

Powerful, classy, reliable – the new **SOMMER** garage door operator.



sprint evolution: item no. 2600V000

▶ modern design in stylish black housing

▶ motor control unit with integrated radio receiver (FM 868.8 MHz) and illumination

▶ with automatic obstacle detection, accident prevention, emergency release and controlled soft run



Technical data:

▶ *sprint evolution*

Max. traction and pressure force:	550 N
Max. speed:	160 mm/s
Pluggable motor control board:	AC 230 V, 50 Hz
Power consumption:	60-220 W
Power consumption at nominal load (165 N):	140 W
Temperature range:	-20°C/+60°C
Illumination:	32.5 V / 34 W
Modulated soft run:	yes
Door types:	retractable door, sectional door, canopy door and side-hinge door
Max. door height of retractable door:	2,600 mm
with rail extension (available as accessory):	3,350 mm
Max. door height of sectional door:	2,350 mm
with rail extension (available as accessory):	3,100 mm
Max. door width:	4,200 mm



Last updated: 02/2010. Literal errors, errors and technical changes excepted.

SOMMER
DOOR & GATE AUTOMATION

Visit our homepage: www.sommeruk.com

SOMMER Door & Gate Automation UK Ltd.
3 Stirling Park • Bleriot Way • Clifton Moor
York • YO30 4WU
phone: 01904 476 330
fax: 01904 476 331
email: enquiries@sommeruk.com